



Commercial Hot Dip Galvanized Pipe
 (Specification: British Standard 1387: 1985)

Pipe Size O.D.	Wall Thickness	Length	Pieces Per Bundle	Lbs/Ft
1-3/8"	0.083"	20', 21', 24'	91	1.043
1-3/8" SOE	0.083"	10'6", 21'	91	1.043
1-3/8"	0.100"	21'	91	1.298
1-5/8"	0.083"	20', 21', 24'	61	1.334
1-5/8" SOE	0.083"	10'6", 21'	61	1.334
1-5/8"	0.100"	21'	61	1.666
1-7/8"	0.083"	8', 18', 21', 24'	61	1.536
1-7/8"	0.100"	24'	61	1.922
2-3/8"	0.083"	8', 18', 20', 21', 24'	37	1.940
2-3/8"	0.100"	18', 21', 24'	37	2.430
2-7/8"	0.125"	9', 10', 18', 20', 21', 24'	19	3.560
3-1/2"	0.125"	10', 18', 20', 21', 24'	12 or 19	4.330
1-3/8"	0.133"	21'	60	1.678

Schedule 40 Hot Dip Galvanized Pipe
 (Specification: ASTM A53 Grade A)

Pipe Size O.D.	Wall Thickness	Length	Pieces Per Bundle	Lbs/Ft
1-5/8"	0.140"	21'	42	2.273
1-7/8"	0.145"	9', 18', 21', 24'	36	2.718
2-3/8"	0.154"	8', 8'6", 9'6", 10'6", 17', 18', 19', 20', 21', 24'	26	3.680
2-7/8"	0.203"	17', 18', 20', 21', 24'	18	5.793
3-1/2"	0.216"	10', 18', 20', 21', 24'	14	7.576
4-1/2"	0.237"	21', 21', 24'	10	10.790
6-5/8"	0.280"	20', 21', 24'	7	18.974